



2 MP IP Bullet CAMERA

AY-MCR-IP-183

MICRO
SERIES



FEATURES

- 1 | 2.4" 2 MEGAPIXEL PROGRESSIVE CCD Sensor
- FULL HD RESOLUTION, 12 MM FIXED LENS
- SMART IR, 40 MTRS IR DISTANCE
- AGC, BLC, DWDR, MASKING, MOTION DETECTION, ANTI FOG
- METAL CASING, INDOOR, POE
- ONVIF COMPLIANT

FEATURES

| Camera | |
|------------------------|--|
| IMAGE SENSOR | 2 MP IP Bullet CAMERA (XM2235/12MM/Smart IR) 40mtr |
| ILLUMINATION | Color: O.Q1Lux @(F1.2,AGC ON),O LUX with IR |
| LENS | 12 MM LENS |
| IR DISTANCE | 40 MTRS |
| ELECTRONIC SHUTTER | AUTO (1/25S-1/100000S ADJUSTABLE) |
| DAY/NIGHT | AUTO/COLOUR/B&W |
| S/N RATIO | _ > 55 DB |
| NOISE REDUCTION | 2D/3D DIGITAL NOISE REDUCTION |
| ANTI FOG | YES |
| WDR | DIGITAL WDR |
| IMAGE ADJUSTMENT | SHARPNESS, BRIGHTNESS, SATURATION, CONTRAST ADJUSTABLE |
| VIDEO ENCODING | H.264 |
| ENCODING TYPE | H.264-HIGH PROFILE/MAINPROFILE/BASE LINE |
| RECORD RESOLUTION | 1080P@25FPS |
| VIDEO BIT RATE CONTROL | SUPPORT VBR/CBR |
| VIDEO BIT RANGE | 32KBPS-8152KBPS |
| ZOOM | DIGITAL |

| | |
|-----------------------|---|
| NETWORK INTERFACE | RJ 45 10M/100M ADAPTIVE ETHERNET INTERFACE |
| MOTION DETECTION | MULTIPLE DETECTION ZONE, VARIABLE SENSITY LEVELS |
| ROI | SUPPORT |
| SNAPSHOT | JPEG CAPTURE, CAPTURE RESOLUTION IS THE MAX CODING RESOLUTION |
| SECURITY FEATURES | SUPPORT PASSWORD PROTECTION, |
| TEXT OVERLAY | SUPPORT (CHANNEL NAME AND TIME TITLE) |
| MOBILE APP | IOS, ANDROID |
| NETWORK FUNCTION | 1Pv4 1Pv6, HTIP, HTIPS, 802.1x, Qos, FTP, SMTP, UPnP, SNMP, DNS, DONS, NTP, RTSP, RTP, TCP, UDP, IGMP ICMP DHCP PPPoE |
| PROTOCOL | SUPPORT ONVIF PROTOCOL |
| PROTECTION GRADE | Ip66 |
| POWER | DC 12V |
| OPERATION TEMPERATURE | (-10'C-60'C(14'C-122'C) |
| POWER SUPPLY | 8W MAX |

**Product housing specifications are subject to change without prior notice.

**Note: Image in the datasheet is only for reference. Real image of product may vary.



www.ayrusglobal.com