

## 2Megapixel IP Camera



AY-PRO-DA2MP

PRO  
SERIES

### Key Features

- > Sony 1/2.8" CMOS Sensor
- > Triple Codec ( H.265 / H.264 / MJPEG)
- > Streaming : RTP over RTSP, Unicast RTP, Multi cast RTP
- > Support to Onvif latest Version
- > Built in PoE
- > IP66 (weather Proof)
- > 2D/3D DNR, True WDR (120dB)

### Technical Specifications

SPECIFICATION	
<b>Video Encoding</b>	
Image Device	Sony 1/2.8" CMOS Sensor
Vido Encoding	H.265 Main Profile/MJPEG/ H.264HighProfile/Main Profile/BaseLine Profile
Maximum Image Output	Main stream : 1920*1080@25/30fps, two Auxiliary Streams can choose.
Steaming transmission	Three stream
Video Bite Rate	32Kbps~8MkPs
<b>Image Enhancement</b>	
Min. Illumination	color 0.01 Lux @ F1.2 ( AGC On) Black and White 0.001Lux @ F1.2 ( AGC On)
LED	-
Electronics Shutter Speed	Auto (1/25~ 1/10,000)
DNR	2D and 3D DNR
Day / Night	Auto/color/B&W (Built-in IR_CUT)
WDR	Support True WDR ( 120dB)
Video adjust	sharpness, Brightness, Saturation, Contrast
backlight compensation	Support
<b>LENS</b>	
Focal Length	Megapixel f=3.6mm
<b>Functions</b>	
Motion Detection	Multiple detection zones, variable sensitivity levels
Screen shots	JPEG, Capture resolution is max coding resolution
Security	Password protection and water marker
OSD	Yes ( channel Name and Time)
Intelligent function	support network abnormal detection, privacy masking
Mobile App	VSSMOBILE for both iphone and Android
Protocol support	TCP/IP ; UDP ; HTTP ; IGMP ; ICMP ; DHCP ; RTP/RTSP ; DNS ; DDNS ; FTP ; NTP ; PPPPOE ; UPNP ; SMTP ; SNMP
Web interface	Ethernet 10/100M port (RJ-45)

Others	
Lightning Protection	Power supply, Lan, POE all lightning protection, meets with standard GB/T17626.5. and IEC61000-4-5
Current Consumption	DC 12V / POE (-P) < 1.8W (without IR LED)
Operating Temp	-10°C ~ +75°C
Storage Temp	-20°C ~ +80°C
Dimension (WxH)	Ø (90 + 138) x 105H
Weight	300g

### Dimension

